MPO-MPO MULTIMODE CABLE DATASHEET

Brief Introduction

Round cable (also called bundle cable or trunk cable) MPO-MPO jumpers can be 4 to 24 core fibers. The OM3 cable is aqua color and the material is LSZH. The outer diameter is ∮3.0mm. For the polarity, there are three types: Type-A, Type-B, and Type-C. For the connection between 40G optical modules, which is usually Type-B(Key up – Key up). MPO connector can be male or female. MPO to MPO Pre-Terminated cable is designed for 40/100G QSFP+ SR4, 40G QSFP+ CSR4 and 100G QSFP28 SR4 fiber optical module direct connection and high density data center.

Features

1. High quality ferrule and accurate alignment PIN and PIN hole.
2. Standard Loss (IL ≤ 0.7dB) and Low loss (IL ≤ 0.35dB) are available.
3. The Connector end-face meets the interference index.
4. Connector compliant with IEC 61754-7(Type MPO connector family).

Applications


1. High density cabling data center.
2. Cabling in communication base station and distribution case.
3. Jumper connection.
4. 40G and 100G optics system, QSFP module.
5. Optical fiber communication system, CATV, LANs and WANs, FTTx

Specifications

Connector A	MPO Male or Female	Connector B	MPO Male or Female
I.L. (Standard Loss)	≤0.70dB(0.40dB Typ.)	Return Loss	≥25dB
I.L. (Low Loss)	≤0.35dB(0.20dB Typ.)	Return Loss	≥25dB
Polish Type	PC to PC	Minimum Bend Radius	10mm
Repeatability	≤0.10dB	Interchangeability	≤0.20dB
Durability	≤0.20dB typical change, 500 mating		
Core number	4, 6, 8, 10, 12, 24cores, customized		
Fiber Mode	OM3/OM4/OM5	Test Wavelength	850/1300nm
Attenuation at 850nm	≤2.3dB/km	Attenuation at 1300nm	≤0.6dB/km
Cable Jacket	LSZH	Cable Jacket O.D	3.0mm
Installation Tensile Load	120N	Long-Term Tensile Load	50N
Operating Temperature	-20°C to +70°C	Storage Temperature	-40°C to +85°C

Note: MTP Connector is available.

It is necessary to confirm whether MPO connector is male or female before production.



MPO Connector: Female (Without Guide Pin)




MPO Connector: Male (With Guide Pin)

According to ANSI-TIA-568-C.3-2008 specifications, there are three types about polarity: type-A, type-B and type-C, show as the figure. This should be confirm before production.


Type-A arry patch cord fiber sequence

Connector	Fiber Sequence (Viewing the end face of the connector with key up)											
A	1	2	3	4	5	6	7	8	9	10	11	12
B	13	14	15	16	17	18	19	20	21	22	23	24
A	13	14	15	16	17	18	19	20	21	22	23	24
B	1	2	3	4	5	6	7	8	9	10	11	12




Type-B arry patch cord fiber sequence

Connector	Fiber Sequence (Viewing the end face of the connector with key up)											
A	1	2	3	4	5	6	7	8	9	10	11	12
B	24	23	22	21	20	19	18	17	16	15	14	13
A	13	14	15	16	17	18	19	20	21	22	23	24
B	12	11	10	9	8	7	6	5	4	3	2	1



Type-C arry patch cord fiber sequence


Connector	Fiber Sequence (Viewing the end face of the connector with key up)											
A	1	2	3	4	5	6	7	8	9	10	11	12
B	14	13	16	15	18	17	20	19	22	21	24	23
A	13	14	15	16	17	18	19	20	21	22	23	24
B	2	1	4	3	6	5	8	7	10	9	12	11



Our Packing



Black Velcro Tape twine cable



Anti-static ziplock bag



Put ziplock bag neartly in cartons



Good cartons for transport

Order information

connector1	Male or Female	connector2	Male or Female	Cores	Fiber Type	Core/Cladding	Module	Cable Type	Type A,B,C	I.L. Grade	Cable Material	Color	Length
MPO	Male	MPO	Male	4	OS2	9/125	Single Mode	trunk	Type A	I.L.＜0.70dB	PVC	Purple	1m(3ft)
MTP	Female	MTP	Female	6	OM5	50/125	Multimode	ribbon	Type B	I.L.＜0.35dB	LSZH	Aqua	2m(7ft)
				8	OM4	62.5/125		breakout	Type C		OFNP(Plenum)	Orange	3m(10ft)
				12	OM3							Blue	4m(13ft)
				24	OM2							Yellow	5m(16ft)
				48	OM1							Lime Green	6m(20ft)
				72	G.657A2								7m(23ft)
				96	G.657A1								8m(26ft)
					G.652D								9m(30ft)
													10m(33ft)
													others